



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ

## PRIORITY DOCUMENT

SUBMITTED OR TRANSMITTED IN  
COMPLIANCE WITH RULE 17.1(a) OR (b)

REC'D 07 JUN 2004

WIPO

PCT

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


BEST AVAILABLE COPY


Signed

*Andrew Gersey*

Dated

12 May 2004





17NOV03 032511-7 D02903  
P01/7700 00-0326651.7

The Patent Office

Cardiff Road  
Newport  
South Wales  
NP10 8QQ

## Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference	11360P1 GB/MH		
2. Patent application number (The Patent Office will fill this part in)	0326651.7		15 NOV 2003
3. Full name, address and postcode of the or of each applicant (underline all surnames)	Reckitt Benckiser (UK) Limited 103-105 Bath Road Slough Berkshire SL1 3UH United Kingdom  Patents ADP number (if you know it)  If the applicant is a corporate body, give the country/state of its incorporation 07972136002 ✓ England		
4. Title of the invention	Device and Method		
5. Name of your agent (if you have one)	Marina Hall Reckitt Benckiser plc Group Patents Department Dansom Lane Hull HU8 7DS United Kingdom  Patents ADP number (if you know it) 7799521001		
6. Priority: Complete this section if you are declaring priority from one or more earlier patent applications, filed in the last 12 months.	Country	Priority application number (if you know it)	Date of filing (day / month / year)
7. Divisionals, etc: Complete this section only if this application is a divisional application or resulted from an entitlement dispute (see note d)	Number of earlier UK application		Date of filing (day / month / year)
8. Is a Patents Form 7/77 (Statement of inventorship and of right to grant of a patent) required in support of this request?	Yes		
Answer YES if a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body. Otherwise answer NO (See note d)			

## Patents Form 1/77

9. Accompanying documents: A patent application must include a description of the invention. Not counting duplicates, please enter the number of pages of each item accompanying this form:

Continuation sheets of this form

Description	21
Claim(s)	2
Abstract	1
Drawing(s)	3

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for a preliminary examination and search (Patents Form 9/77) One

Request for a substantive examination (Patents Form 10/77) One

Any other documents (please specify) FS1

11. I/We request the grant of a patent on the basis of this application.

Signature(s)

*John Crawford McKnight*  
John Crawford McKnight

Date 14 November 2003

12. Name, daytime telephone number and e-mail address, if any, of person to contact in the United Kingdom

Marina Hall 01482 582855

Marina.Hall@ReckittBenckiser.com

### Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

### Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered YES in part 8, a Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- Part 7 should only be completed when a divisional application is being made under section 15(4), or when an application is being made under section 8(3), 12(6) or 37(4) following an entitlement dispute. By completing part 7 you are requesting that this application takes the same filing date as an earlier UK application. If you want the new application to have the same priority date(s) as the earlier UK application, you should also complete part 6 with the priority details.

**DUPLICATE****Device and Method**

This invention relates to a device for removing a composition from the skin, and to an associated method.

5 The invention relates in particular, but not exclusively, to a device for use in a depilatory method.

Hair removing compositions are widely available. They may be epilatory, and effect hair removal by mechanical  
10 action. They may be depilatory, and effect hair removal by causing hair degradation by chemical action.

In the case of depilatory compositions, the user applies these to their skin, leaves them for a pre-determined  
15 interval to allow them to work, and then removes them from the skin, usually using a article which is provided. This is typically a cloth, sponge or a elastically flexible plastics sheet. Such a plastics sheet may be formed with a curvature so as to facilitate removal of the composition  
20 and the hair entrained within it. However some consumers find such a device messy or difficult to use. Many hold such devices close to their leading edge which contacts the skin and consequently it is difficult for them to keep their hand clear of the composition and hair being  
25 removed. Furthermore it can be difficult to reach some areas, such as parts of the backs of legs, using such devices.

We have now devised a different type of device to remove  
30 compositions from the skin, including depilatory compositions, efficiently and cleanly.

In accordance with a first aspect of the present invention there is provided a device for removing a composition from the skin, the device comprising: a non-shaving head which in use is moved over the skin to effect removal of the composition; a handle; and a joint between the head and the handle, permitting the head to articulate about the handle.

In this specification when we use terms such as "downward" and "underside" we are referring to the side of the device which faces the skin, in use. Terms such as "upwardly" and "upper" denote the opposite direction. The head is regarded as the front of the device and the tip of the handle as the rear of the device.

A preferred device is designed for use in hair removal; to be drawn over skin to which a depilatory composition has been applied, in order to remove, after any required interval, hair and the depilatory composition. Whilst the device may effect the breaking of some hairs which have been weakened by the depilatory composition it cannot be used as a shaving device. Accordingly it does not have a cutting blade.

Preferably, however, it has the general appearance of a shaving device. Thus it preferably has a generally stick-like or wand-like handle, and a wider head. Preferably the maximum width of the head is 50% greater than the maximum width of the handle, preferably at least 80% greater.

The head suitably has a leading edge which, in use, makes contact with the skin. Preferably this is a straight edge. The leading edge is preferably generally parallel

to but maximally displaced from the joint. By parallel to the joint we allude to an axis about which articulation takes place.

5 Preferably the leading edge is angular but not sharp, to the extent that it might effect cutting, either of skin or hair. Thus, by eye when viewed in magnification it can be seen to be radiused, in preferred embodiments. Preferably the radius of such a leading edge is at least 0.25mm, more  
10 preferably at least 0.5mm, and most preferably at least 0.65mm. Preferably the radius of such a leading edge is up to 1.5mm, more preferably up to 1mm, and most preferably up to 0.85mm. It may be a compound radius, for example having a major radius in accordance with the  
15 definitions given above and a minor radius, smaller than the major radius, at the distal tip of the leading edge. Preferably such a minor radius is up to 0.5mm, more preferably up to 0.3mm, most preferably less than 0.25mm. Preferably it is at least 0.1mm, more preferably at least  
20 0.15mm.

Preferably the head is firmly carried by the handle; in the absence of a force or when merely touched there is no tendency for it to be deflected. In use when bearing upon  
25 the skin it may articulate against a resistance force.

In use, the user holds the handle and places the leading edge of the head on the skin. Typically the arrangement is such that the head, and the device as a whole, make an  
30 acute angle to the skin when the device is in position to be drawn across the skin, in the rearwards direction. The force applied by the head to the skin is provided by the user to the handle, and this is transmitted by the joint,

to the head. Preferably the head may articulate upwardly, so that the usage is still comfortable, and not mechanically aggressive to the skin. The extent of articulation preferably depends on the force applied.

- 5 Thus the joint is preferably such that when the head is in contact with skin, a downward force applied to the handle is always delivered to the head, whatever position the head has moved to; and in each position of the head it experiences a resistance force from the joint.

10

Preferably at an extreme position articulation of the head towards the handle is terminated. This may be achieved by provision of a stop means or resilient means within the joint.

15

- Preferably, movement of the head about the handle in the opposite direction, so as to splay open the joint, is limited. This may suitably be by the provision of resilient means within the joint preventing it from articulating excessively.

20

- Suitably resilient means, for example a packing or moulding of an elastomeric material, may be present in the joint such that there is a resilient hindrance to articulation of the head excessively in either direction, about the handle.

25

- Preferably the head articulates about its rear edge region, where it connects to the joint, preferably about its rear edge itself.

30

Suitably the head is able to articulate relative to the handle (by which we mean from its unflexed or rest

position to its maximally flexed - that is, maximally articulated - position when in use) through an angle of at least  $1^{\circ}$ , preferably at least  $5^{\circ}$ , and more preferably at least  $10^{\circ}$ . Yet more preferably the head is able to  
5 articulate relative to the handle through an angle of at least  $25^{\circ}$ , and most preferably at least  $40^{\circ}$ .

Suitably the head is able to articulate relative to the handle through an angle of up to  $120^{\circ}$ , preferably up to  
10  $90^{\circ}$ , and more preferably up to  $75^{\circ}$ . Most preferably the head is able to articulate relative to the handle through an angle of up to  $60^{\circ}$ .

Suitably when the head articulates about the handle the  
15 leading edge is able to move through an arc of at least 2mm, preferably at least 3mm, more preferably at least 6mm. Yet more preferably when the head articulates about the handle the leading edge is able to move through an arc of at least at least 10mm, and most preferably at least  
20 15mm.

Preferably when the head articulates about the handle the leading edge is able to move through an arc of up to 50mm, preferably up to 40mm, and most preferably up to 30mm.  
25

Preferably the device has a memory property, such that once the force on the head is reduced or removed it is able to recover its previous or rest position. Thus the device may be of a material which is elastic or  
30 elastomeric.

We do not exclude embodiments in which the head is separate from the handle. Preferably, however, the device



is unitary. A unitary device may be formed of one material or it may be formed of more than one material, set together in the manufacture but thereafter inseparable unless the device is destroyed or damaged. For example  
5 the handle may be formed of a generally rigid plastics material which carries on at least a part of its outer surface an elastomeric material, for improved feel. The elastomeric material may suitably be formed with grip-assisting formations, for example one or more of fins,  
10 ribs, grooves and bumps.

Typically the leading edge is a 20-60mm line, preferably 30-50mm.

15 Preferably the head is curved when viewed from the side. Preferably it is downwardly concave.

Preferably the handle is curved when viewed from the side. Preferably it is downwardly concave.

20

Preferably the device as a whole is curved, preferably being downwardly concave, with the curvature of the head preferably leading smoothly into the curvature of the handle.

25

Preferably the device is formed from a plastics material, especially a thermoplastics material. Polyolefins are especially suitable, notably polyethylene (HDPE or LDPE) and, especially polypropylene. Such materials allow the  
30 preferred resistive articulation of the head about the handle, allow for elastic recovery, are readily moulded, and are tough, having little tendency to brittle failure, as might otherwise take place within the joint.

Copolymers or polymer blends may be used.

Preferably the device is formed from a plastics material  
5 having a Flexural Modulus of at least 0.8 GPa, more  
preferably in excess of 1 GPa.

Preferably the device is formed from a plastics material  
having a Flexural Modulus of up to 1.5 GPa, more  
10 preferably up to 1.2 GPa.

Preferably the device is formed of a plastics material  
having a Melt Flow Index of at least 10 g/10 mins, more  
preferably at least 18 g/10 mins.

15

Preferably the device is formed of a plastics material  
having a Melt Flow Index of up to 30 g/10 mins, more  
preferably up to 25 g/10 mins.

20 Flexural Modulus measures a material's ability to resist  
deformation under an applied load. For the purposes of  
this specification the reference test method is that  
described in ISO 178.

25 Melt Flow Index (MFI) measures how quickly a thermoplastic  
material will flow through a known aperture, at a known  
temperature and under a known pressure. The higher the  
MFI the faster the material will flow. For the purposes  
of this specification the reference test method is that  
30 described in ISO 1133.

The plastics material may contain one or more additives to  
improve its properties for the task in hand. For example

a plasticizer may be added in order to improve its suppleness or flexibility.

Preferably the device is a unitary plastics moulding.  
5 Suitably the joint is achieved by provision of a web of material between the handle and the head, preferably thinner than both.

Preferably the handle is a substantially rigid part.  
10 Preferably the head is a substantially rigid part.  
Preferably, therefore, the articulation of the head about the handle arises substantially wholly because of the nature of the joint; there is substantially no propensity for deflection elsewhere.

15 Preferably the device weighs less than 12g, and more preferably weights less than 8g.

Preferably the handle is of a waisted shape, having a  
20 widened distal region and a widened proximal region (adjacent the joint), with the waist in between. The handle may have a widened distal region which has a non-shaving edge, adapted to effect removal of the composition. The widened distal region is preferably  
25 narrower than the head of the device, so that the user can choose from a wider and a narrower edge, for different parts of the body. Preferably the distal region has a depression to aid holding, most preferably on its upper side. Preferably the proximal end region of the handle  
30 has a depression on its upper side. In each of these cases the depression could be replaced by a textured non-slip surface, which could be moulded in.

The handle could be a solid piece but more preferably it is generally U-shaped, downwardly open.

5 The handle could be adapted to release a fragrance. The fragrance could be moulded into any moulded plastics article or could be adhered to the surface of the handle, for example sprayed onto it. The fragrance could, for example, be in the form of fragrance microcapsules which are ruptured, to release the fragrance, when the device is  
10 grasped.

Preferably the joint is formed by a web of the plastics material, suitably at the base of a notch which is open in the upwards direction. The notch could be of U-section or  
15 V-section. The walls of the notch may be formed by the end faces of the handle and the head. Limitation of flexure in the sense of the head towards the handle may arise simply by the closure of the notch, as by abutment of the facing ends of the head and the handle.  
20 Alternatively the notch may be packed or moulded with an elastomeric material to put limits on the articulation of the head in both directions.

Alternatively, the head may be connected to the handle by  
25 a flexible connection of a serpentine form, in which the "windings" are closely pitched. The windings thereof may be packed or moulded with an elastomeric material to put limits on the articulation of the head in both directions.

30 Preferably the head is bounded by the joint, by the leading edge, which is preferably wider than the joint, and by lateral edges between them. Preferably the lateral edges of the head are convex. The convex edges may have

corresponding curved walls upstanding from them,  
preferably being tallest near to the joint and tapering  
towards the frontal corners of the head (that is, the  
junctions between the convex lateral edges and the leading  
5 edge). Preferably the head has the appearance of a circle  
or ellipse truncated by the leading edge.

The junctions between the leading edge of the head and the  
adjoining edges may be radiused, to reduce the risk of  
10 them jaggng against the skin.

The device may, in principle, be used to remove any  
composition from the skin, for example a cleansing or  
moisturising body pack. However it will be evident from  
15 the foregoing that the primary interest is in relation to  
the removal of a depilatory composition, along with  
entrained hair.

In accordance with a second aspect of the present  
20 invention there is provided a method of removing a  
composition from the skin, in particular a depilatory  
composition containing hair, by use of a device of the  
first aspect.

25 In accordance with a third aspect of the present invention  
there is provided a method of effecting depilation,  
comprising the steps of:

applying a depilatory composition to the skin;

30

allowing it to remain on the skin for a pre-determined  
interval;

removing the depilatory composition and depilated hair by moving a device as defined in the first aspect over the skin; and

5 rinsing the skin.

Preferably the method is one in which, in addition to the depilatory action of the depilatory composition, there is an additional hair removing action of an epilatory nature,  
10 achieved by the device. The device is preferably not epilatory in its action in the absence of a depilatory composition; but preferably it is epilatory in its action in conjunction with a depilatory composition, to the extent that hairs weakened by the depilatory composition  
15 may be removed by the device. This is potentially very useful because it means that the depilatory composition need only be left on the skin for a reduced period - for example 3 minutes. A longer period would usually be  
20 required if the depilatory composition was required to remove all of the treated hair growth, but this would carry with it an increased risk of causing skin irritation. In accordance with the present invention a shorter period can be used in the knowledge that the device can complete the task.

25

The depilatory composition described herein may for example be a cream, lotion, gel or foam.

The device could be sold on its own. Preferably, however,  
30 it is sold in a pack with a receptacle of the composition which is to be applied to the skin. The receptacle may for example be a jar or tube; a conventional aerosol canister; or a multi- or bi-compartment aerosol product

(in which the composition and a compressed gas are segregated, inside the canister, the compressed gas driving out the composition when a valve is operated). In the case of a depilatory composition the latter is a preferred way of supplying the composition.

A pack of a composition to be applied to the skin and a device of the first aspect could be a carton with the two components in, or it could be a clear plastics package encompassing them (blister pack, or shrink sleeve). Alternatively the device of the first aspect could be engaged directly with the receptacle which contains the composition. For example a canister could have a modified cap to which the device is secured.

15

In accordance with a fourth aspect there is provided a pack comprising a device as defined above and a depilatory composition.

20 The invention will now be further described, by way of example, with reference to the accompanying drawings, in which:

Fig. 1 shows a first embodiment of device, in perspective view;

25

Fig. 2 shows the device of Fig. 1, in side view;

Fig. 3 shows a second embodiment of a device, in perspective view;

30

Fig. 4 shows a third embodiment of device, in side view;

Fig. 5 is a view from the underside, of the device of Fig. 4;

Fig. 6 shows a fourth embodiment of the device, in  
5 perspective view;

Fig. 7 shows the device of Fig. 6 in plan view;

Fig. 8 shows the device of Fig. 6 in side view;

10

Fig. 9 is a cross-section through line D-D of Fig. 8;

Fig. 10 is a cross-section through line E-E of Fig. 8;

15 Fig. 11 is an expanded view of Detail A shown in Fig. 8;

Fig. 12 is an expanded view of Detail B shown in Fig. 6;

Fig. 13 is an expanded view of Detail C shown in Fig. 8;  
20 and

Fig. 14 shows a device coupled to a canister of a  
depilatory composition.

25 Each of the embodiments to be described is intended for  
use with a depilatory composition.

The device of the first embodiment shown in Figs. 1 and 2  
comprises a wide head 2 and a stick-like handle 4,  
30 connected together by a joint 6 which acts as a hinge,  
permitting the head to articulate about the handle on  
application of a force, and against a resistance force.  
It will be seen in Fig. 2 that the head and handle



terminate in end faces which join together at their lower edges at the joint 6. The end faces in effect define the joint as a V-shaped notch, upwardly open.

5 The general appearance of the device is similar to that of a razor device, in having the head 2, which is of similar width to the head of a razor device, and the much narrower stick-like handle 4. However the device is not, in fact, a razor device. It does not have any metallic cutting  
10 blade(s).

As can be seen in Fig. 2 the device is generally curved in side view, being concave when considered from the downward direction.

15

The device is a one-part polyolefin moulding. The head 2 and the handle 4 are both generally rigid, whilst the joint 6 is thinner, and is flexible. Thus the head 2 may articulate or flex relative to the handle 4, the  
20 articulation being wholly provided by virtue of the flexibility of the joint 6.

The head 2 has a leading edge region 8, on its opposite side from the joint 6. The leading edge region 8  
25 terminates in a leading edge 10, 44mm long in this embodiment. The leading edge 10 is formed with a radius of 0.75mm. This radius means that although good removal of a material from the skin by a scraping action can be achieved, and substantially weakened hairs might be broken  
30 and removed, undegraded hairs could not be cut or broken, nor could skin be. Between the leading edge 10 and the joint 6 the head has outwardly curved or bowed side edges 12, such that the overall plan view shape of the head is

approaching semi-circular. On its upper face the head has a bulbous part 14. This is present for aesthetic reasons and to impart rigidity to the head.

5 The handle is of solid plastics material, and is somewhat waisted in shape, having a wide and thick, rounded, distal region 16 of width 22mm, a narrowed waist 18 of width 10mm, and a proximal region 20 which is wider than the waist, widening to a maximum width of 18mm, this being  
10 immediately adjacent the joint 6. The upper face of the proximal region 20 is moulded with a non-slip textured portion 22. This can be seen in Fig. 1. As can be seen in Fig. 2 this textured portion rises towards the joint 6. The net result is that the textured portion 22 provides a  
15 comfortable location for the thumb 24 of a user, and facilitates application of a force during use. Meanwhile the user's fingers 26 are located on the concave underside of the handle.

20 In use a depilatory composition (for example a cream, lotion, foam or gel) is applied to the skin, usually by hand, and is left for the required period of time. This is usually five minutes although we favour the use of a depilatory composition which is formulated for removal in  
25 three minutes. The device described above is then used to remove the composition, together with depilated hairs. The device is moved rearwardly over the skin, by a drawing action, in the manner of a wet razor. The downward force applied by the user to the handle is transmitted to the  
30 head, whose leading edge is in contact with the skin. The head flexes slightly, to the position shown in dotted lines in Fig. 2, as a reaction to the force acting between the head and the leading edge of the skin. If the user

applies a higher downward force the head flexes more. In essence the head is self-correcting, against the risk of pressing too hard against the skin. The articulation of the head relative to the handle takes place against the resistance within the joint. If there were no resistance, the head would be floppy on the handle and the device would be of no use.

If an extremely high downward force were applied to the head it could conceivably articulate to its limit position, in which the V-shaped notch has closed; the end face of the handle in effect acting as a stop means. However this is not intended in this embodiment and is not characteristic of any expected use.

The handle could be held in different positions. For example it is designed to be comfortable for a user also to hold the distal end of the handle between thumb and fingers so that the leading edge is well beyond the tips of the fingers. This may be useful when removing material from areas which are difficult to reach, for example the backs of legs.

In the first embodiment the polyolefin is polypropylene but in other embodiments of similar design polyethylene, for example LDPE or HDPE, may be preferred.

The embodiment shown in Fig. 3 differs from that of Fig. 2 only in the provision of an elastomeric fin 28, at the leading edge. It may be of any elastomeric material and may be set into the product in any typical way, for example by dual shot moulding. Preferably it is fairly

firm and/or narrow, so that the provision of the joint still provides benefit.

Figs. 4 and 5 show a third embodiment which is also closely related to the first embodiment. Only the significant differences will be described. In other respects the description of the first embodiment applies to the third embodiment.

A first difference is that the handle is not of solid plastics, but is a downwardly concave moulding. That is, in transverse cross-section it is U-shaped. Fig. 5 is a view from underneath the device and this shows walls 30, 32 and a recess 34 between them. This means that the volume of plastics used in the device can be reduced from about 11cm<sup>3</sup> to about 7cm<sup>3</sup>, and provides improved grip.

A second difference is that the distal end 16 of the device is formed with a recess 36. This is to aid the holding of the device at the distal end, as described in relation to Fig. 1. The outline of this recess can be seen in the underside view of Fig. 5, along with the underside of the textured portion 22.

A third difference is in the joint 6, which is not in the form of a V-shaped notch. The end faces of the handle and the head do not meet, as they did in the first and second embodiments. Instead they are joined together by a short bridge 38. The joint is in effect in the form of a U-shaped notch. This gives good flexibility and, because the location of articulation is more diffuse, a lower risk of stress damage.

The underside of the head, adjacent to the joint 6, is formed with a crescent-shaped part 40 which increases its rigidity.

- 5 A fifth difference is that the joint is filled with a resilient packing 41, bonded into the joint. The resilient packing limits the flexure of the head about the handle, in both directions, that is, clockwise and anticlockwise.

10

Figs 7 to 13 show a fourth embodiment which is also closely related to the first embodiment. Only significant further details will be described. In other respects the description of the first embodiment applies to the fourth  
15 embodiment.

The first difference is that the head has, extending upwardly from its outwardly curved side edges 12, an upstanding wall 42. Although it is not shown clearly in  
20 the drawings - but can be seen to some extent in Fig. 6 - the wall rises obliquely from the main sheet region 46 of the head, at an angle of approximately 60° thereto. This wall is tallest adjacent to the joint 6, and diminishes or tapers towards the front corners 44, 46, at respective  
25 ends of the leading edge 10. At those corners 44, 46 the wall 42 disappears.

Like the third embodiment, the fourth embodiment has a handle which is downwardly concave, as shown by Figs. 9  
30 and 10, which are cross-sections taken through the handle. At section D-D shown in Fig. 9 the maximum width of the handle is 21mm, and the maximum width of the concavity 47 formed in the underside of the handle is 15mm. The

maximum height of the handle is 13.5mm and the depth of the cavity is 8mm. At section E-E shown in Fig. 10 the maximum width of the handle is 11mm, and the maximum width of the concavity 47 formed in the underside of the handle is 6mm. The maximum height of the handle is 5mm and the depth of the cavity is 2mm.

The device of the fourth embodiment also differs from that of the first embodiment in that the corners 44, 46 at the front of the head are more markedly radiused, to reduce the risk of snagging against the skin. Fig. 12 shows the corner 44 in a detailed view. The radius of each corner is 3mm in this embodiment.

Fig. 11 shows the leading edge 10 in a detailed cross-sectional view. This is of complex shape. The main sheet region 46 is of thickness 1.5mm (dimension a). Approaching the edge 10, the upper surface is bevelled as at 48, and the length of this bevel is 3.2mm (dimension b). The bevel leads into a first radiused region (dimension c),  $r=0.8\text{mm}$ , and this leads in turn to a more sharply radiused region,  $r=0.2\text{mm}$  which connects to the under surface of the sheet region 46 (dimension d). The thickness of the head measured at the junction of the bevel 48 and the first radiused region, is dimension e, 0.8mm.

Fig. 13 is a detailed sectional view of the joint 6. This is made up of a under surface 50 having a radius of 4mm and an upper surface 52, representing the upwardly open base of the joint, having a radius of 1.5mm. The thickness of the material at the base of the joint is 1mm.

The width of the leading edge is 44mm. The length of the handle, measured up to the mid-point of the joint, is 99mm. The handle is waisted. At its distal end the maximum width is 23mm. At its proximal end, immediately adjacent  
5 the hinge, its width is 18mm. In between its "waist" has a minimum width of 10mm. The overall length of the device is 123mm.

In this fourth embodiment the polymer is a polypropylene  
10 random copolymer, having the following properties:

Flexural Modulus 1050 MPa (ISO 178)

Melt Flow Index: 21 g/10 mins (ISO 1133)

The device shown in Fig. 6 was tested in conjunction with  
15 a glycolate-containing depilatory lotion. The lotion was applied to a 50mm x 50mm test area already marked in pen on the legs of female volunteers, who had allowed their leg hair to grow. It was left for 3 minutes then removed. In Test 1 the lotion was removed by rinsing, without use  
20 of the device or any other manual aid. In Tests 2 and 3 the lotion was removed by means of the device, drawn over the skin against the direction ("grain") of hair growth. The results are as follows:

25 Test 1:        Before - 95 hairs counted in test area  
                 After - 88 hairs counted in test area

Test 2:        Before - 90 hairs counted in test area  
                 After - no hairs counted in test area

30

Test 3:        Before - 95 hairs counted in test area  
                 After - no hairs counted in test area

Fig. 14 shows a device generally in accordance with the four embodiments described above secured to a canister of a depilatory composition. The canister is not a conventional aerosol canister but is a bi-compartment aerosol canister. Between the removable cap 142 and canister body 144 there is entrapped a flexible plastics part 144 which is formed so as to retain a device in accordance with the invention. The whole assembly is enveloped in a plastics film, for example as a blister pack. An advantage of this arrangement is that there is no possibility of rotation of the assembly prior to purchase. In an alternative arrangement in which these two parts are within one package, but in separate compartments, there would be a risk that the canister would turn within the package, due to its cylindrical shape. If this happened the presentation to the customer at the point of sale would be spoilt.

In another embodiment a similar result is achieved by using two moulded transparent plastics shells which are engaged together to envelop a canister and a device as described above, the shells together defining a cavity for snug receipt of the canister, and a cavity for the snug receipt of the device. The cavities can be separate but are preferably interconnected, such that the device is nested against the canister, substantially as shown in the Figure 14 embodiment.



CLAIMS

1. A device for removing a composition from the skin, the device comprising: a non-shaving head which in use is  
5 moved over the skin to effect removal of the composition; a handle; and a joint between the head and the handle, permitting the head to articulate about the handle.
2. A device as claimed in claim 1, wherein there is a  
10 resistance force acting against articulation of the head, which resistance force increases as the articulation increases.
3. A device as claimed in claim 1 or 2, wherein the head  
15 is able to articulate about the handle through an angle in the range 10 to 40°.
4. A device as claimed in any preceding claim, wherein  
20 when a force causing articulation of the head is reduced or removed the head is able to recover its previous or original position.
5. A device as claimed in any preceding claim, the device  
25 being unitary.
6. A device as claimed in claim 5, the device being a one-part plastics moulding.
7. A device as claimed in any preceding claim, wherein  
30 the handle is substantially rigid, the head is substantially rigid, and the joint is the only source of the articulation.

8. A device as claimed in any preceding claim wherein the joint is formed by a web of plastics material at the base of an upwardly open notch between the handle and the head.

5 9. A method of removing a composition from the skin by use of a device as claimed in any preceding claim.

10. A method of effecting depilation, comprising the steps of:

10

applying a depilatory composition to the skin;

allowing it to remain on the skin for a pre-determined interval;

15

removing the depilatory composition and depilated hair by moving a device as defined in any of claims 1 to 8 over the skin; and

20

rinsing the skin.

11. A pack comprising a device as claimed in any of claims 1 to 8 and a depilatory composition.

25 12. A pack as claimed in claim 11, wherein the depilatory composition is supplied in a bi-compartment aerosol canister.

30 13. A device, method or pack substantially as hereinbefore described with particular reference to the accompanying drawings.

**ABSTRACT****Device and method**

5

A device for removing a depilatory or other composition from the skin comprises: a non-shaving head (2) which in use is moved over the skin to effect removal of the composition; a handle (4); and a joint (6) between the  
10 head and the handle, permitting the head to articulate about the handle.

(Fig. 1)

15

20

Fig. 1.

1/3




Fig. 2.





Fig. 3.



2/3

Fig. 8




Fig. 7




Fig. 6





Fig. 12. DETAIL B

SECTION E-E

DETAIL C





Fig. 9



SECTION D-D

3/3

Fig. 4.



Fig. 5.





Fig. 6.



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**